

Fiber Access Terminal- FATM-0109R

COMCAST  **GROUP**



Contents

Description3

Features3

Configuration4

 Standar Accessories.....4

 Optional Accessories4

Description

FATM-0109R fiber access termination box is able to hold up to 9 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- The box casing is made of industrial plastic PP+GF material.
- Outdoor application and good UV resistant.
- Plug and play installation, easy for maintenance and expansion.
- 9 x reinforced adapters for drop cable with reinforced connectors.
- Minimum fiber bending radius: 35mm
- 180-degree access with 2 pcs of buckled lock structure
- Designated position for the placement of 2pcs of 1x8 splitter
- Protection grade: IP65.
- 1 x cable entrances for distribution cable gland (8-13.5mm)

Configuration

Model	FATM-0109R
Material	PP+GF
Size	A*B*C (mm) 290*210*78
Max capacity	Splice 96 Fibers (4 trays x 24FO)
	PLC Splitter 2 pcs 1x8 (SC)
Reinforced Adapters (SC)	9 Pcs SC/UPC or SC/APC
Weight	1.2 Kg
Color	Black

Standard Accessories

- Splice trays x 2 pcs.
- wall mounted kits
- Fiber protective sleeves
- Cable protection tube
- Key
- PG 13.5 cable glands for distribution ports

Optional Accessories

Pole Mounted kits