

# T-OT560-A26D MINI OTDR

**COMCAST** GROUP



## Instrument characteristics :

- Nine-in-one function
- The 4.3-inch full-view capacitive touch screen supports multi-touch
- Cover plate type tempered glass panel, don't worry about screen scratch
- Support horizontal version, vertical version, perfect fusion of the two habits of user operations
- Support charging treasure charging, do not worry about the battery is not enough
- In line with the international standards of test data with perfect simulation software, so that your report more simple
- Sink type light port design, so that the instrument light port to get better protection
- Support U disk, SD card and Micro USB export data protection
- Any interface supports screen capture

## Physical indicators :

- 4.3-inch capacitive touch screen with full viewing , TFT 800x480 resolution
- Lithium battery: 5200mAh/ 3.7v, standby time > for 10 hours
- Size: 175x105x45mm, weight: 560g (including battery)
- Working temperature: -10~+55°C, storage temperature: -20~+80°C

## Technical indicators

Model No.	Wavelength	Dynamic Range	Max. Test Range
TOT560-A26D	1310/1550nm	26/24dB	100km
Measuring range	100m、500m、2km、5km、10km、20km、40km、80km/90km		
Sampling resolution	Minimum: 0.2m		
Event dead zone	< 2.0m		
Attenuation dead zone	< 7.0m		
The sampling point	64,000 point		
Linearity	≤0.05dB/dB		
Loss threshold	0.01dB		
Loss resolution	0.001dB		
Range resolution	0.01m		
Range accuracy	±(0.5m+Rangex3×10 <sup>-5</sup> +Sampling resolution) (Excluding refractive index error)		
Memory	>40000		
Data interface	2 USB(Type A×1, Micro USB×1, SD card)		
Screen	4.3-inch TFT-LCD (Standard distribution capacity touch screen)		
Battery	3.7V/5200mAh		
Temperature	Working temperature: -10°C~+55°C; Storage temperature: -20°C~+80°C		
Humidity	≤95% (No condensation)		
Size/Weight	175x105x45mm / 0.56kg (Contain the battery)		

OPM	Type A: +10dBm~-70dBm;Type B: +26dBm~-50dBm
VFL	10mW, CW/2Hz
LS(Laser Source)	The output power: -5dBm, Modulation frequency: CW/270Hz/1KHz/2KHz
Network Cable test	Support network wire sequence testing and wire alignment

## Accessories

Standard	FC adaptor, Power adapter, Lithium battery, USB cable, Quick guide, Portable package
----------	---

Please visit our website [www.comcast-sa.com](http://www.comcast-sa.com) or contact your local sales representative.

### **Comcast México**

Overseas Sales Subsidiary  
Cal. Lázaro Cárdenas #1309  
Col. Colón industrial CP.44940  
Guadalajara, Jalisco  
Tel. +52 33 38607059  
Info.mx@comcast-sa.com

### **Comcast Guatemala**

Overseas Sales Subsidiary  
Av. Hincapié 28-45 zona 13  
Guatemala city 01013  
Tel. +506 4004 1400  
Gerente.gua@comcast-sa.com

### **Comcast Nicaragua**

Overseas Sales Subsidiary  
3ra. Entrada las Colinas, Embajada  
De cuba 1C, Este, Casa #34  
Mangua, Nicaragua  
Te, +1809 5711033  
Admin.nic@comcast-sa.com

### **Comcast El Salvador**

Overseas Sales Subsidiary  
51 Av. Norte # 159 entre calle  
poniente y Av. Roosevelt  
San Salvador, El Salvador  
Tel. +503 7950 4882  
Info.sc@comcast-sa.com

### **Comcast Dominican Republic**

Overseas Sales Subsidiary  
Av. Nuñez de Cáceres #2 Plaza  
Comercial Pradosur, Local 102  
Santo Domingo, Dominican Republic  
Te.+ 1 809 571 1033